


THE FLEXIBLE INSULATION WITH SILVER FINISH
FOR BETTER AESTHETICS

ArmaFlex® Class 0 Alu

Reliable insulation material with aesthetically appealing silver finish for cleanroom environments.

- // Easy to clean
- // Durable and high resistance to mechanical abuse
- // Aesthetically appealing silver finish
- // Very high water vapour diffusion resistance, $\mu \geq 12,000$
- // Excellent fire resistance
- // Class 0 fire classification according to BS 476 Parts 6 and 7
- // Effectively reduces thermal and energy loss

www.armacell.in



 **armacell®**
ArmaFlex®

THE FLEXIBLE INSULATION WITH SILVER FINISH FOR BETTER AESTHETICS

ArmaFlex Class 0 Alu

Highly flexible, closed-cell insulation material with very high water vapour diffusion resistance of $\mu \geq 12,000$. FM-Approved. Aesthetically appealing silver finish that is durable and resilient against mechanical abuse.

Aesthetically appealing



Easy to Install



Easy to Clean



Benefits

// Energy efficient

Low thermal conductivity minimizes energy losses to give long term energy savings.

// Closed-cell structure

Minimizes moisture penetration to ensure long-term protection against corrosion under insulation.

// Condensation control

High resistance to water vapour ensures that the surface temperature remains above dew point, removing the need for an additional water vapour barrier.

// Aesthetically appealing

Durable foil facing is resistant to mechanical abuse and offers aesthetically appealing finish.

// Easy to install

Highly flexible elastomeric foam that can be installed quickly on irregular shapes and installations in tight spaces.



TECHNICAL DATA - ARMAFLEX CLASS 0 ALU

Brief description	Highly-flexible, closed-cell insulation material with high water vapour diffusion resistance and low thermal conductivity.					
Material type	Elastomeric foam based on synthetic rubber (NBR), with reinforced Aluminium Foil facing.					
Colour	Silver					
Material special information	Laminated with 12 micron aluminium foil, with reinforced glass scrim.					
Product range	Available in rolls (sheet) of 1m width and thicknesses of 6mm, 9mm, 13mm, 16mm, 19mm, 25mm and 32mm thicknesses. Self-adhesive rolls are also available as well as tubes of 1m length and 9mm, 13mm, 19mm, 25mm and 32 mm thicknesses.					
Applications	Prevent condensation and enable energy efficiency through insulation of air-conditioning systems such as air ducts, especially for pharmaceutical industry or cleanroom environments.					
Special features	Bright silver finish and smooth surface; attracts less dust, is easy to clean and has high resistance to mechanical abuse.					
Assembly	ArmaFlex can be used together with a variety of ArmaFlex adhesives such as, ArmaFlex Pipe Seal / ArmaFlex Duct Seal / ArmaFlex 520 adhesive and ArmaFix for a complete insulation system. Please refer to the ArmaFlex installation manual for advice.					
Property	Value/Assessment					Standard/Test method
Temperature range						
Service temperature	Maximum service temperature	+105 °C		+85 °C if sheet or tape is glued to the object with its entire surface		Tested according to EN 14706, EN 14707, EN 14304
	Minimum service temperature	0 °C				
Thermal conductivity						
	9m	0	+20	+40	[°C]	Tested according to EN 12667, EN ISO 8497
	λ ≤	0.035	0.037	0.039	[W/(m·K)]	
Water vapour diffusion resistance						
Water vapour diffusion resistance factor	μ ≥ 12,000					Tested according to EN 12086, EN 13469
Water absorption						
Water absorption (by volume)	0.2%					Tested according to ASTM C 1763, ASTM C 209
Fire performance and approvals						
Fire performance according to building regulations	Class 0					Tested according to BS 476 Part 6:1989
Fire propagation	Total index performance (I) ≤ 12 Sub index (i _i) ≤ 6					
Surface spread of flame	Class 1					Tested according to BS 476 Part 7:1997
Flammability	HB, V-0					Tested according to UL-94
FM-approved	Yes					Tested according to FM 4924
Practical fire behaviour	Self-extinguishing, does not drip and does not spread flames.					
Other technical features						
Resistance to mechanical impact	Good					
Chemical behaviour	Excellent resistance to ozone, oil and chemicals (consult product test list).					
UV resistance	Not recommended for outdoors.					
Environmental aspect [†]	Zero ozone depletion potential, zero global warming potential.					
Storage	Shall be stored in dry and clean area, away from direct sunlight.					

All data and technical information are based on results achieved under typical application conditions. Recipients of this information should, in their own interest and responsibility, clarify with us in due time whether or not the data and information apply to the intended application area. Installation instructions are available in our ArmaFlex installation manual.

¹ All data and technical information are provided above are based on results achieved under tests certified by the respective testing authorities for base foam only and not the complete system.

Contact information or visiting card



All data and technical information are based on results achieved under the specific conditions defined according to the testing standards referenced. It is the customer's responsibility to verify if the product is suitable for the intended application. The responsibility for professional and correct installation and compliance with relevant building regulations lies with the customer. Armacell takes every precaution to ensure the accuracy of the data provided in this document and all statements, technical information and recommendations contained within are believed to be correct at the time of publication. By ordering/receiving product you accept the **Armacell General Terms and Conditions of Sale** applicable in the region. Please request a copy if you have not received these.

© Armacell, 2020. ® and ™ are trademarks of the Armacell Group and is registered in the European Union, United States of America, and other countries.

00124 | ArmaFlex Class 0 Alu | ArmaFlex | TDS | 072020 | IN | EN

ABOUT ARMACELL

As the inventors of flexible foam for equipment insulation and a leading provider of engineered foams, Armacell develops innovative and safe thermal, acoustic and mechanical solutions that create sustainable value for its customers. Armacell's products significantly contribute to global energy efficiency making a difference around the world every day. With 3,135 employees and 24 production plants in 16 countries, the company operates two main businesses, Advanced Insulation and Engineered Foams. Armacell focuses on insulation materials for technical equipment, high-performance foams for high-tech and lightweight applications and next generation aerogel blanket technology.



Scan QR code for digital copy

For more information, please visit:
www.armacell.com

 **armacell**[®]
ArmaFlex[®]