



SPECIFICATION TABLE:

Product code	Pipe Size		Hanger Rod	Cross Bolt Dia x Length (CRD x CRL)
	Size (Inch)	Outer Dia(mm)		
CH-UL	1/2"	22	10	8.00 x 45.00
CH-UL	3/4"	28	10	8.00 x 55.00
CH-UL	1"	34	10	8.00 x 65.00
CH-UL	1.1/4"	42	10	8.00 x 70.00
CH-UL	1.1/2"	48	10	8.00 x 80.00
CH-UL	2"	59	10	8.00 x 85.00
CH-UL	2.1/2"	75	12	10.00 x 110.00
CH-UL	3"	89	12	10.00 x 130.00
CH-UL	4"	115	12	10.00 x 150.00
CH-UL	6"	168	16	12.00 x 220.00
CH-UL	8"	219	16	12.00 x 270.00

CONSTRUCTION FEATURES:

- Made with Mild steel. [ cold rolled coils – CRC ]
- Finished Electro galvanized 15+ microns (Galvanized Zinc Plating) [ Hot dip galvanized if required ]
- SS – 304 / 316 can be manufactured on request.

TECHNICAL SPECIFICATION:

- Maximum Temperature should be 650°F (343°C)
- Electro galvanized as per ASTM B 633 Standards
- Conforms to Federal Specification WW-H-171E & A-A-1192A, Type 1 and Manufacturers Standardization Society ANSI/MSS SP-69 & SP-58, Type 1

APPLICATIONS:

- Recommended for the suspension of non-insulated pipe or insulated pipe with a B3151 shield.
- Pipe will not ‘pinch’ when installing.
- 15° swing in either direction allows pipe to easily feed through.
- Engineered design aligns bolt holes for quicker overhead installation.

